



Bowers & Wilkins

702 S3

Technical Information



Technical features

Decoupled Carbon Dome tweeter
Solid Body Tweeter-on-Top
Continuum™ cone FST™ midrange
Decoupled midrange
Aerofoil™ Profile bass cones
Flowport™

Description

3-way vented-box system

Drive units

1x ø25mm (1in) Decoupled Carbon Dome high-frequency
1x ø150mm (6in) Continuum cone FST midrange
3x ø165mm (6.5in) Aerofoil Profile bass

Frequency range

28Hz to 33kHz

Frequency response

(+/-3dB from reference axis)

46Hz - 28kHz

Sensitivity

(on axis at 2.83Vrms at 1m)

90dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 86Hz - 28kHz
<0.5% 110Hz - 20kHz

Nominal impedance

8Ω (minimum 3.1Ω)

Recommended amplifier power

30W - 300W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 1010mm (39.8in) cabinet only
1138mm (44.8in) including tweeter and plinth

Width: 192mm (7.6in) cabinet only
290mm (11.4in) including plinth

Depth: 354mm (13.9in) cabinet only
391mm (15.4in) including grille and terminals
410mm (16.1in) including plinth

Net weight

33.5kg (73.8lbs)

Finishes

Cabinet: Gloss black
Satin white
Mocha
Rosenut (APAC only)

Grille: Black
Grey (Satin White only)