



Setting new standards for compact home theatre

Forming the basis of a completely revised Mini Theatre concept, the new M-1 combines a cleaner aesthetic with dramatically improved performance. Combine it with either the ASW608 or the new PV1D subwoofer to create a home theatre experience with superb integration and impressive power for such a discreet system. Plus, its more extended bass response allows M-1 to be used on its own for two-channel applications. Mount the speaker as shown on a table or shelf. Alternatively, a bracket is included for wall mounting and a floor stand is available as an optional extra.



Technical Specifications

Technical features	Nautilus™ tube loaded tweeter with aluminium dome Woven glass fibre cone bass / midrange
Description	2-way vented-box system
Drive units	1x 25mm (1in) aluminium dome high-frequency 1x 100mm (4in) woven glass fibre cone bass / midrange
Frequency range	-6dB at 55Hz and 50kHz
Frequency response	64Hz - 23kHz ±3dB on reference axis
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	85dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 120Hz - 30kHz
Nominal impedance	8Ω (minimum 4.0Ω)
Crossover frequency	4kHz
Recommended amplifier power	20W - 100W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 248mm (9.8in) Width: 114mm (4.5in) Depth: 162mm (6.4in) Mounted on table stand
Net weight	2.3kg (5lb)
Finishes	Cabinet: Matte Black or Matte White Grille: Matte Black or Matte White perforated steel to match